



TYPICAL PROPERTY DATA SHEET
BP FLEX 8000 VP BIK

Product Information: Our BP Flex 8000 VP BIK material is a general purpose partially crosslinked thermoplastic elastomer using recycled content to achieve maximum economic value and performance.	Appearance: Black
Product Features: Injection molding or extrusion applications	Forms: Pellets
Processing Guide available upon request.	

PHYSICAL	UNIT	OTHER INFORMATION	TEST METHOD	NOMINAL VALUES
SPECIFIC GRAVITY	g/cc		ASTM D-792	0.92
SHORE HARDNESS	Shore A		ASTM D-2240	80
MOISTURE	%			0.1

Typical values should not be construed as a guarantee analysis of any specific lot or as specification items. The properties of any single lot or shipment of product may vary from the above typical analysis. All information contained herein is accurate and to the best of our knowledge. However, Buckeye Polymers, Inc. assumes no liability, nor makes any guarantee to the accuracy or completeness of the information contained herein. Final determination as to the suitability of any information, or use of material, is solely the responsibility of the user.

Buckeye Polymers can custom compound a material to meet your specifications.

**Buckeye
Polymers, Inc.**

104 Lee Street
Lodi, Ohio 44254
Phone (330)948-3007
Fax (330)948-2037
www.buckeyepolymers.com